

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously Presented) An image forming device comprising:
 - a main casing having a first surface and a second surface opposing the first surface;
 - a processing unit that is detachably mounted in the main casing and that forms images on a recording medium;
 - a first power source circuit board disposed inside the main casing, the first power source circuit board outputting a drive voltage to the processing unit; and
 - a second power source circuit board disposed inside the main casing, wherein the components of the first power source circuit board generate a larger amount of heat than the second power source circuit board;
 - the first surface is formed with a first exhaust outlet exhausting air from the main casing; and
 - the first power source circuit board is disposed downstream of the second power source circuit board in an air passage direction in which the air passes through the main casing and is discharged through the first exhaust outlet.
2. (Original) The image forming device according to claim 1, wherein the components of the first power source circuit board include at least one of a transformer and a regulator.
3. (Original) The image forming device according to claim 2, wherein the second power source circuit board is a high-voltage power source circuit board.
4. (Original) The image forming device according to claim 1, wherein the first power source circuit board has heat dissipating plates that dissipate heat generated by the

components of the first power source circuit board, the heat dissipating plates being disposed such that a largest surface of each heat dissipating plate is disposed along the air passage direction.

5. (Original) The image forming device according to claim 1, further comprising a drive motor that generates a driving force, wherein the second surface of the main casing is formed with an intake hole through which air is supplied into the main casing, the air flowing over the first power source circuit board and being exhausted through the first exhaust outlet, the drive motor being disposed near the intake hole.

6. (Original) The image forming device according to claim 1, further comprising a first fan disposed in confrontation with the first exhaust outlet for exhausting air from the main casing.

7. (Original) The image forming device according to claim 6, further comprising a second fan, wherein the first surface of the main casing is formed with a second exhaust outlet, and the second fan is disposed in confrontation with the second exhaust outlet of the main casing for exhausting air from the main casing.

8. (Original) The image forming device according to claim 7, further comprising a first partitioning wall, wherein the main casing defines an internal space, and the first partitioning wall separates the internal space into a first air path formed by the first fan and a second air path formed by the second fan.

9. (Original) The image forming device according to claim 7, further comprising:

a conveying unit that conveys the recording medium in a conveying direction;

and

a fixing unit that is disposed downstream of the processing unit in the conveying direction and that fixes the images onto the recording medium, wherein

the second fan is disposed closer to the fixing unit than to the processing unit.

10. (Original) The image forming device according to claim 9, wherein the second fan is disposed above the fixing unit.
11. (Original) The image forming device according to claim 9, further comprising a second partitioning wall that is provided between the fixing unit and the processing unit.
12. (Original) The image forming device according to claim 11, wherein the second partitioning wall includes two walls disposed between the fixing unit and the processing unit, the two walls defining an air passage therebetween, and the second fan exhausts the air having passed through the air passage.
13. (Original) The image forming device according to claim 11, wherein the main casing defines an internal space, and the second partitioning wall partitions the internal space into a third air path on the processing unit side and a fourth air path on the fixing unit side.
14. (Original) The image forming device according to claim 13, further comprising an ozone filter disposed in the third air path.
- 15-25. (Canceled)
26. (Previously Presented) The image forming device according to claim 1, wherein the first power source circuit board is disposed adjacent the first exhaust outlet.